



# 规格书

## SPECIFICATION

|               |        |                         |
|---------------|--------|-------------------------|
| CUSTOMER NAME | 客户名称:  |                         |
| CUSTOMER NO.  | 客户编号:  |                         |
| SERIES        | 系 列:   | 滑动开关卧式侧拨                |
| MODEL NO.     | 型 号:   | XB-SK-22H26             |
| DRAWING NO.   | 图 形 号: | Slide Switch Horizontal |

If specification of this product meets your request, please confirm all the items of it and return to us with signature and stamp, it will be basis of our production and record. Thanks your cooperation in advance!

若此产品规格符合贵司要求，敬请确认此规格书内所有项目  
并签名和盖章后回传给我司，以作我司产品制作之

依据和存档之用，多谢合作！

### EXAMINE & APPROVAL 审批

|                                                                                 |                        |
|---------------------------------------------------------------------------------|------------------------|
| <b>APPROVE</b> 接受                                                               | <b>NOT APPROVE</b> 不接受 |
| <br><br><br><br><br><br><br><br><br><br>SIGNATURE 签署      STAMP 盖章      DATE 日期 |                        |

|                 |               |                |                |
|-----------------|---------------|----------------|----------------|
| PREPARED BY.制表人 | CHECKED BY.校对 | APPROVED BY.审核 | APPROVAL BY.批准 |
| 研发部             | 品质部           | 工程部            | 总经办            |
| 戴海明             | 黄自清           | 庞军             | 吴量             |
| 2022. 06. 08    | 2022. 06. 08  | 2022. 06. 08   | 2022. 06. 08   |

东莞市溪榜电子有限公司

# Dong guan Xi Bang Electronics Co., Ltd

地址：广东省东莞市黄江镇合路工业区

**Address:He Lu Industrial Zone, Huangjiang Town  
Dongguan City, Guangdong Province**

**Tel: (0769)82055138/82056828**

**Fax:(0769)83663452**

邮箱: [admin@alspr.com](mailto:admin@alspr.com)    [switch@alspr.com](mailto:switch@alspr.com)

<http://www.alpsr.cn/>    <http://www.alpsr.com/>

Dong Guan XB ElectronicsCo., Ltd

AccountNumber: 705540238

BankName: CitibankN. A., HongKongBranch

Country/Region: Hong Kong


BankCode:006

BankAddress: 3GardenRoad, Central, Hong Kong


SWIFT/BIC: CITIHKHX (CITIHKHXXXX\*If 11 characters are required)

MAIL: HK@ALPSR.CN XB@ALPSR.CN

## Quality core! Afterburner for Made in China!



### SCHEMATIC (NON-SHORTING)



P.C.B LAYOUT  
BOTTOM VIEW

注: "□"表示关键尺寸(7个).

|                                                                                                                                                                                                                                                                   |              |                |      |           |                                              |  |  |  |            |           |                          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------|------|-----------|----------------------------------------------|--|--|--|------------|-----------|--------------------------|
| 8                                                                                                                                                                                                                                                                 |              |                |      |           | TOLERANCE                                    |  |  |  |            |           |                          |
| 7                                                                                                                                                                                                                                                                 |              |                |      |           | UNLESS SPECIFIED                             |  |  |  |            |           |                          |
| 6                                                                                                                                                                                                                                                                 | SPRING PLATE | PBS STRIP      | 1    | NATURAL   |                                              |  |  |  |            |           |                          |
| 5                                                                                                                                                                                                                                                                 | CONTACT CLIP | PBS STRIP      | 2    | Ag PLATED | WITHIN 1.5mm : ±0.1mm<br>OVER 1.5mm : ±0.2mm |  |  |  | A          | 2012-8-14 | 初 版                      |
| 4                                                                                                                                                                                                                                                                 | TERMINAL     | BRASS STRIP    | 8    | Ag PLATED | TITLE : HORIZONTAL SLIDE SWITCH              |  |  |  | ISSUE      | DATE      | DESCRIPTIONS OF REVISION |
| 3                                                                                                                                                                                                                                                                 | BASE         | PHENOLIC RESIN | 1    | NATURAL   |                                              |  |  |  | UNIT : mm  |           | DRWG NO.: XB-SK-22H26    |
| 2                                                                                                                                                                                                                                                                 | KNOB         | POM            | 1    | BLACK     | MODEL: XB-SK-22H26                           |  |  |  | SCALE: 3:1 | DWN.      |                          |
| 1                                                                                                                                                                                                                                                                 | FRAME        | STEEL STRIP    | 1    | Ni PLATED |                                              |  |  |  |            |           |                          |
| NO.                                                                                                                                                                                                                                                               | PARTS        | MATERIALS      | Q'TY | FINISH    |                                              |  |  |  |            |           |                          |
| <div><div><div><div>东莞市溪榜电子有限公司</div><div>DONG GUAN XI BANG ELECTRONI CS CO., LTD.</div><div>Switch Connector</div></div></div><div><div>CHK'D</div><div>APPD.</div></div></div> |              |                |      |           |                                              |  |  |  |            |           |                          |

|                                                                                                                                               |                                        |                                                                                                                                                                                                                                       |                                                                                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
|  <b>东莞市溪榜电子有限公司</b><br>DONG GUAN XI BANG ELECTRONICS CO., LTD. |                                        | 文件编号                                                                                                                                                                                                                                  | XB-SK-20150116-01                                                                                                                          |
|                                                                                                                                               |                                        | 发布日期                                                                                                                                                                                                                                  | 2015 年 01 月 16 日                                                                                                                           |
| SPECIFICATION 规格书                                                                                                                             |                                        | 第 A 版                                                                                                                                                                                                                                 | 第 1 页 共 3 页                                                                                                                                |
| MODEL NO. 产品名称: XB-SK-22H26 高温金码                                                                                                              |                                        |                                                                                                                                                                                                                                       |                                                                                                                                            |
| DRAWN 制订                                                                                                                                      |                                        | 吴工                                                                                                                                                                                                                                    | APPD. 审核 庞军                                                                                                                                |
| 1、RATING (额定值)                                                                                                                                |                                        | : DC 50V 0.3A                                                                                                                                                                                                                         |                                                                                                                                            |
| 2、FUNCTION (接触型式)                                                                                                                             |                                        | : 2P2T                                                                                                                                                                                                                                |                                                                                                                                            |
| 3、TIMING (时间特性)                                                                                                                               |                                        | : SHORTING                                                                                                                                                                                                                            |                                                                                                                                            |
| 4、ELECTRICAL CHARACTERISTICS (电气性能规格)                                                                                                         |                                        |                                                                                                                                                                                                                                       |                                                                                                                                            |
| ITEM 项目                                                                                                                                       |                                        | TEST CONDITIONS 测试条件                                                                                                                                                                                                                  | PERFORMANCE 规格                                                                                                                             |
| 4.1                                                                                                                                           | CONTACT RESISTANCE<br>接触电阻             | MEASURED AT 1KHz SMALL CURRENT (100mA OR LESS)<br>在 1KHz 微小电流 (100mA 以下) 测试.                                                                                                                                                          | 100mΩ MAX.<br>100 毫欧以下                                                                                                                     |
| 4.2                                                                                                                                           | INSULATION RESISTANCE<br>绝缘电阻          | APPLY A VOLTAGE OF 500V DC FOR 1 MIN.<br>TO FOLLOWING PORTIONS AFTER WHICH<br>MEASUREMENT SHALL BE MADE.<br>(1) BETWEEN BODY AND TERMINAL.<br>(2) BETWEEN TERMINALS.<br>输入 500V DC 电压 1 分钟, 按以下接触方法测试:<br>(1) 排脚相互之间。<br>(2) 排脚与外壳之间。 | 100MΩ MIN.<br>100 兆欧以上.                                                                                                                    |
| 4.3                                                                                                                                           | DIELECTRIC STRENGTH<br>耐电压             | AC 500V rms (50-60Hz) FOR 1 MIN TRIP CURRENT: 0.5mA<br>(1) BETWEEN TERMINALS.<br>(2) BETWEEN INDIVIDUAL TERMINAL AND FRAME.<br>输入 AC 500V (50-60Hz) 电压, 1 分钟感度电流为 0.5mA,<br>按以下接触方法测试:<br>(1) 排脚相互之间<br>(2) 排脚与外壳之间.                  | WITHOUT DAMAGE TO PARTS<br>ARCING OR BREAKDOWN<br>ETC<br>没有绝缘破坏等异常                                                                         |
| 5、MECHANICAL CHARACTERISTICS (机械性能规格)                                                                                                         |                                        |                                                                                                                                                                                                                                       |                                                                                                                                            |
| ITEM 项目                                                                                                                                       |                                        | TEST CONDITIONS 测试条件                                                                                                                                                                                                                  | PERFORMANCE 规格                                                                                                                             |
| 5.1                                                                                                                                           | OPERATING FORCE<br>作动力                 | MEASUREMENT SHALL BE MADE AT THE NEAREST POINT OF<br>THE COMPONENT OR AT THE POINT 3mm FROM THE TIP OF<br>THE ACTUATOR (KNOB).<br>在距离胶柄前端 3mm 作测定点.                                                                                   | 250gf ± 100gf                                                                                                                              |
| 5.2                                                                                                                                           | TERMINAL STRENGTH<br>端子强度              | A STATIC LOAD OF (500gf) SHALL BE APPLIED<br>TO THE TERMINAL FOR 15 SEC, IN ANY DIRECTION.<br>在排脚前端任意一个方向加 500gf 力度测试, 时间为<br>15 秒.                                                                                                   | MECHANICAL AND<br>ELECTRICAL<br>CHARACTERISTICS SHALL<br>BE SATISFIED WITHOUT<br>LOOSENESS<br>OF ACTUATOR.<br>在端子中没有裂开, 松动等异常, 满足于机械、电器性能。 |
| 5.3                                                                                                                                           | DISPLACEMENT OF ACTUATOR (KNOB)<br>柄强度 | A STATIC LOAD OF 10N (1Kg) SHALL BE APPLIED<br>TO THE TOP OF THE ACTUATOR (KNOB) AND THEN<br>DISPLACEMENT SHALL BE MEASURED TO THE<br>DIRECTION OF THE ARROW.<br>在柄的前端施加 1Kg 的力度, 位移应沿印记的方向上定.                                        | THE LEVER SHALL HAVE<br>NO SERIOUS DEFORMATION<br>AND FUNCTION IS<br>NORMALLY.<br>柄部无严重变形, 可以正常工作                                          |

|                                                                                                                                                                      |                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                 |                       |                |                      |       |     |                      |        |     |                                                                               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|----------------|----------------------|-------|-----|----------------------|--------|-----|-------------------------------------------------------------------------------|
| <div></div> <div>东莞市溪榜电子有限公司</div> <div>DONG GUAN XI BANG ELECTRONICS CO., LTD.</div> |                                            | 文件编号                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | XB-SK-20150116-01                                                                                                                                                                                                                                                                                                               |                       |                |                      |       |     |                      |        |     |                                                                               |
|                                                                                                                                                                      |                                            | 发布日期                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 2015 年 01 月 16 日                                                                                                                                                                                                                                                                                                                |                       |                |                      |       |     |                      |        |     |                                                                               |
| SPECIFICATION 规格书                                                                                                                                                    |                                            | 第 A 版                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 第 2 页 共 3 页                                                                                                                                                                                                                                                                                                                     |                       |                |                      |       |     |                      |        |     |                                                                               |
| 6、ENDURANCE CHARACTERISTICS (耐久性)：                                                                                                                                   |                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                 |                       |                |                      |       |     |                      |        |     |                                                                               |
| ITEM 项目                                                                                                                                                              |                                            | TEST CONDITIONS 测试条件                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | PERFORMANCE 规格                                                                                                                                                                                                                                                                                                                  |                       |                |                      |       |     |                      |        |     |                                                                               |
| 6.1                                                                                                                                                                  | LIFE TEST<br>寿命试验                          | WITHOUT LOAD:<br>AN ACTUATOR SHALL BE SUBJECT TO 10,000 CYCLES AT A SPEED OF 15 TO 18 CYCLES FOR 1 MIN.<br>无负荷:<br>操作者以每分钟 15—18 回的频率作 10,000 回之无负荷测试.                                                                                                                                                                                                                                                                                                                                                                                                                             | (1) CONTACT RESISTANCE(接触电阻)<br>200mΩ MAX. 200 毫欧以下.<br>(2) INSULATION RESISTANCE(绝缘电阻)<br>50MΩ MIN. 50 兆欧以上..<br>(3) WITHSTAND VOLTAGE(耐电压)<br>AC 500V, 1 MINUTE.AC 500V 1 分钟<br>(4) OPERATING FORCE(作动力)<br>±30%INITIAL VALUE.<br>变化范围初始值±30%<br>(5) WITHOUT DAMAGE TO PARTS ARCING OR BREAKDOWN ETC.<br>(测试后外表无损伤, 并且满足机械性能) |                       |                |                      |       |     |                      |        |     |                                                                               |
| 6.2                                                                                                                                                                  | SOLDERABILITY TEST<br>可焊性试验                | THE TOP OF THE TERMINALS SHALL BE DIPPED 2mm IN THE SOLDER BATH OF 230±5℃ FOR 3±0.5 SECONDS.<br>端子顶部被浸入锡焊池中 2mm 深, 温度为 230±5℃, 时间为 3±0.5 秒.                                                                                                                                                                                                                                                                                                                                                                                                                                        | THE AREA OF SOLDERING SHOULD BE OVER 75%<br>焊接面积要有 75%以上.                                                                                                                                                                                                                                                                       |                       |                |                      |       |     |                      |        |     |                                                                               |
| 6.3                                                                                                                                                                  | RESISTANCE TO SOLDERING HEAT TEST<br>耐焊性试验 | (1). TEMPERATURE AND IMMERSING TIME<br>温度及浸锡时间 <table><tr><td></td><td>TEMPERATURE<br/>温度 (℃)</td><td>TIME<br/>时间 (S)</td></tr><tr><td>DIP SOLDERING<br/>浸 锡</td><td>260±5</td><td>3±1</td></tr><tr><td>MANUAL SOLDERING 手 焊</td><td>360±10</td><td>3±1</td></tr></table> (2) IMMERSION DEPTH:<br>IMMERSION DEPTH UP TO THE SURFACE OF THE BOARD THICKNESS OF PRINTED WIRING BOARD 1.6mm.<br>浸锡深度:<br>浸锡深度至基板 (PCB) 表面, 基板厚度为 1.6mm. (3) WAVE SOLDERING<br>波峰焊<br>(A) 温度 255±5℃ , 时间 3 到 5.5 秒.<br>(B) PREHEAT TIME SHALL BE 30 SECONDS MAX. AT 100℃MAX.<br>预热温度 100℃以下, 30 秒以内完成. |                                                                                                                                                                                                                                                                                                                                 | TEMPERATURE<br>温度 (℃) | TIME<br>时间 (S) | DIP SOLDERING<br>浸 锡 | 260±5 | 3±1 | MANUAL SOLDERING 手 焊 | 360±10 | 3±1 | THERE SHALL BE NO DEFORMATION OR CRACKS IN MOLDED PART.<br>外观无异常, 满足于机械、电器性能。 |
|                                                                                                                                                                      | TEMPERATURE<br>温度 (℃)                      | TIME<br>时间 (S)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                 |                       |                |                      |       |     |                      |        |     |                                                                               |
| DIP SOLDERING<br>浸 锡                                                                                                                                                 | 260±5                                      | 3±1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                       |                |                      |       |     |                      |        |     |                                                                               |
| MANUAL SOLDERING 手 焊                                                                                                                                                 | 360±10                                     | 3±1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                       |                |                      |       |     |                      |        |     |                                                                               |
| 6.4                                                                                                                                                                  | COLD TEST<br>耐冷试验                          | THE SWITCH SHALL BE STORED AT A TEMPERATURE OF -25±3℃ FOR 48 HOURS.<br>THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.<br>放置在温度-25±3℃中 48 小时后, 再将放置在常温常湿的环境中 1 小时后进行测试.                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                 |                       |                |                      |       |     |                      |        |     |                                                                               |

|                                                                                                                                               |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                          |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
|  <b>东莞市溪榜电子有限公司</b><br>DONG GUAN XI BANG ELECTRONICS CO., LTD. |                                           | 文件编号                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | XB-SK-20150116-01                                                                        |
|                                                                                                                                               |                                           | 发布日期                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 2015 年 01 月 16 日                                                                         |
| SPECIFICATION 规格书                                                                                                                             |                                           | 第 A 版                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 第 3 页 共 3 页                                                                              |
| ITEM 项目                                                                                                                                       |                                           | TEST CONDITIONS 测试条件                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | PERFORMANCE 规格                                                                           |
| 6.5                                                                                                                                           | HEAT TEST<br>耐热试验                         | <p>THE SWITCH SHALL BE STORED AT A TEMPERATURE OF <math>70\pm 2^{\circ}\text{C}</math> FOR 48 HOURS. THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.</p> <p>放置在温度 <math>70\pm 2^{\circ}\text{C}</math> 中测试 48 小时后, 再将放置在常温常湿的环境中 1 小时后进行测试.</p>                                                                                                                                                                     | <p>THERE SHALL BE NO DEFORMATION OR CRACKS IN MOLDED PART.</p> <p>外观无异常, 满足于机械、电器性能.</p> |
| 6.6                                                                                                                                           | HUMIDITY TEST<br>潮湿试验                     | <p>THE SWITCH SHALL BE STORED AT A TEMPERATURE OF <math>40\pm 2^{\circ}\text{C}</math> AND A HUMIDITY OF 90% TO 95% FOR 96 HOURS. THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITION FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.</p> <p>放置 <math>40\pm 2^{\circ}\text{C}</math> 的相对湿度为 90%~95% 环境中 96 小时后, 再将放置在常温常湿的环境中 1 小时后进行测试.</p>                                                                                                                             |                                                                                          |
| 6.7                                                                                                                                           | STANDARD ATMOSPHERIC CONDITIONS<br>测试标准状态 | <p>UNLESS OTHERWISE SPECIFIED.</p> <p>THE STANDARD RANGE OF ATMOSPHERIC CONDITIONS FOR MAKING MEASUREMENTS AND TESTS ARE AS FOLLOWS:</p> <p>(1) AMBIENT HUMIDITY: <math>5^{\circ}\text{C}</math> TO <math>35^{\circ}\text{C}</math></p> <p>(2) RELATIVE HUMIDITY: 45% TO 85%</p> <p>(3) AIR PRESSURE : 86Kpa TO 106Kpa</p> <p>在没有指定的情况下测试温度、湿度、气压如下:</p> <p>(1) 温度为 <math>5^{\circ}\text{C}</math>—<math>35^{\circ}\text{C}</math>.</p> <p>(2) 湿度为 45%—85%.</p> <p>(3) 气压为 86Kpa—106Kpa.</p> |                                                                                          |
| 6.8                                                                                                                                           | PRACTICAL TEMPERATURE RANGE<br>使用温度范围     | <p><math>-16^{\circ}\text{C}</math>~<math>+60^{\circ}\text{C}</math>.</p> <p>在 <math>-16^{\circ}\text{C}</math>~<math>+60^{\circ}\text{C}</math> 温度内使用.</p>                                                                                                                                                                                                                                                                                                                                  |                                                                                          |