

REV	ECN #	DESCRIPTION	DRAWING	APPROVED	DATE
A		NEW RELEASE	DEYI		2012/9/8

NOTES :

- 1.0. RATING :
- 1.1. VOTAGE : 12 VAC (R.M.S.)
- 1.2. CURRENT : 1 AMPERE MAXIMUM PER CONTACT AT 30°C T-RISE
- 1.3. TEMPERATURE : -20°C TO +70°C
- 2.0. ELECTRICAL CHARACTERISTIC :
- 2.1. CONTACT RESISTANCE : 50 MILLIOHMS MAXIMUM INITIAL
- 2.2. INSULATION RESISTANCE : 100 MEGOHMS MINIMUM
- 2.3. DIELECTIC WITHSTANDING VOLTAGE : 500 VAC AT SEA LEVEL
- 3.0. MATERIALS :
- 3.1. CONTACT : COPPER ALLOY
- 3.2. HOUSING : THERMOPLASTIC, GLASS FILLED, 130°C, UL 94V-0 RATED
- 4.0. MECHANICAL :
- 4.1. INSERTION FORCE(PER CONTACT): 300~3000 GRAMS
- 4.2. WITHDRAWAL FORCE(PER CONTACT): 300~3000 GRAMS
- 4.3. DURABILITY ,MINIMUM: MATED 5000 TIMES WITHOUT DEGRADING
- 4.4. CONTACT FORCE, MINIMUM: 80 GRAMS

PRODUCT NO.

PJ04-06 A B 05-01

① ② ③ ④

PRODUCT SERIES:

- ① PJ04: PHONE JACK CONNECTOR H=4.5mm
- ② PIN NO.:
04: 4PIN
06: 6PIN
- ③ MATERIAL:
A: PA-9T
- ④ SERIES NO.:
01: $\varnothing 3.5$ mm 无头 H=4.5mm

CUSTOMER DRAWING



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

GENERAL TOLERANCE X. ± 0.20 .XX ± 0.15 .XXX ± 0.10	DRAWING	DEYI	TITLE: PHONE JACK CONNECTOR 4.5h (无头)	
	APPROVED		P/N: XB-PJ04-06AB05-01	
ANGEL TOLERANCE X. $\pm 3^\circ$.XX $\pm 2^\circ$.XXX $\pm 1^\circ$	DATE	2012.09.08	DRAWING NO. XB-C-PJ04-01	
		UNIT	mm	SCALE
		1:1	SIZE	A4
		SHEET	1 of 1	REV
		A		

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F

E

D

C

B

A

G

F