








H=13.0MM



SECTION A-A




RECOMMENDED PCB LAYOUT
TOP VIEW TOLERANCE: ± 0.05



MATING PLUG
DP550250-0188-60000H

SPECIFICATION:

1. RATING: DC 20V 20A
2. CONTACT RESISTANCE:
30m Ω MAX.(INITIAL)
50m Ω MAX.(FINAL)
3. INSULATION RESISTANCE: 100 M Ω MIN.
4. WITHSTAND VOLTAGE: 500 VAC
5. INSERTION FORCE: 3N~30N
6. EXTRACTION FORCE: 3N~30N
7. DURABILITY: 5,000 CYCLES



E	MYLAR			1
D	GROUND	SUS 304		1
C	SHELL	COPPER ALLOY	Ni 40u"MIN.	1
B	CENTER PIN	BRASS	GOLD FLASH/Ni 40u" MIN.	1
A	HOUSING	HIGH TEMP.THERMOPLASTIC	BLACK	1
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY



UNLESS OTHERWISE
SPECIFIED TOLERANCES

XB 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

DECIMALS:	ANGLES:	DESIGN:	Tony	PART NAME:
DIM	TOL	DIM	TOL	$\Phi 5.5$ 立式 (H=13.0)
X.	± 0.50	X.	$\pm 2^\circ$	DC POWER JACK
X.X	± 0.30	X.X	$\pm 1^\circ$	PART NO.
X.XX	± 0.20	X.XX		XB-DC550250-1076-20000H
X.XXX	± 0.10	X.XXX		SHEET: 1/1 REV.: A1
3RD ANGLE PROJECTION	UNIT: mm	APPROVED	Andy	DRAWING NO
			2022.4.15	

REV.	ECN NO.	DESCRIPTION	DESIGN	DATE
------	---------	-------------	--------	------

拉出方向



备注:

- 材料规格:
 - 载带: $T=0.50\text{mm}$
 - 包装盘: 蓝色
 - 纸箱: $L=385, W=385, H=300$
- 包装数量:
250PCS/卷, 10卷(2500PCS)/箱
- 上盖带拨离力: $0.1\text{N} \sim 0.7\text{N}$ ($10 \sim 70\text{gf}$);
拨离角度: $165^\circ \sim 180^\circ$;
拨离速度: 300mm/分钟.




总共10层

PE袋:

外箱, 1PCS

透明胶带



UNLESS OTHERWISE SPECIFIED TOLERANCES				XGB 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.			
DECIMALS:		ANGLES:		DESIGN:	Tony	PART NAME:	
DIM	TOL	DIM	TOL		2022.4.15	DC POWER JACK	
X.	± 0.50	X.	$\pm 2^\circ$	CHECK:		包装图	
X.X	± 0.30	X.X	$\pm 1^\circ$			PART NO.	
X.XX	± 0.20	X.XX				XB-DC550250-1076-20000H	
X.XXX	± 0.10	X.XXX				SHEET: 1/1 REV.: A1	
3RD ANGLE PROJECTION				UNIT:	mm	APPROVED	Andy-liu
					2022.4.15	DRAWING NO	