








MATERIAL 材料:

HOUSING 外壳: PBT,UL94V-0,GRAY.

TERMINAL 端子: PHOSPHOR BRONZE Ø=0.46MM,GOLD PLATING

MECHANICAL 机械:

DURABILITY 耐用性: 750 CYCLES MIN,12.5MM/MINUTE.

INSERTION FORCE 插入力:2.2KG.F MAX

RETENTION STRENGTH 保持力:7.7KG.F BETWEEN JACK AND PLUG.

OPERATING TEMPERATURE 工作温度: -40°C~+85°C.

STORAGE TEMPERATURE 储存温度: -40°C~+85°C.

ALL CRITICAL DIMENSIONS WITH "M"

ELECTRICAL 电气:

VOLTAGE 电压: 125 VOLTS AC.

CURRENT RATING 电流额定值: 1.5AMP.

DIELECTRIC STRENGTH 介电强度: 1000 VAC RMS 50HZ OR 60HZ,1 MIN

INSULATION RESISTANCE 绝缘电阻: 500 MEGA OHMS MIN.INITIAL

AFTER 500V DC FOR 1 MINUTE.

CONTACT RESISTANCE 接触电阻:SINGLE TERMINAL 30 MILLIOHMS MAX.

INITIAL 50 MILLIOHMS MAX. AFTER DURABILITY TEST.



						DSND		SCALE: N/A	MODEL TYPE: USB 2.0		
						DWN		VIEW:	PART NO.: X44AHIWE1DY4017_1		
						CHKD		UNIT: mm/in	DWG NO.: U221-04XN-4BU05-FS		
						APPD		SIZE: A4	WEIGHT		
REVISIONS						DONG GUAN XI BANG ELECTRONIC CO., LTD			SHEET		
www.alpsr.com www.gdxjdz.com www.xbswitch.com									1/1		
									REVISION		
									A0		