



SPEC:

A. Material:

1. Housing: PBT BLACK

2. Terminal: COPPER ALLOY (2-3 μm) ,Ni PLATED (2.5-3.5 μm)

B. Electrical Characteristics:

1. Rating: 15A 250V~ (UL,CUL)

10A 250V~ (CCC,VDE,SEMKO,NEMKO,FIMKO,DEMKO)

C. Approvals:

UL, CUL, CCC, VDE, SEMKO, NEMKO, FIMKO, DEMKO.

序号	名称	材料	处理	数量	备注
1	DB-14-1塑料件	环阻PBT	黑色	1	
2	DB-14-FL插销	黄铜	镀锡	1	Plating Thickness 40u" -80u"
3	DB-14-FS插销	黄铜	镀镍	2	Plating Thickness 40u" -80u"
4	DB-14-D05铁架	锰铜	镀镍	1	Plating Thickness 40u" -80u"

普通公差:

COMMON TOLERANCE :

UP TO 5	±0.20
ABOVE 5 TO 30	±0.30
ABOVE 30	±0.50
ANGULAR	±5°



东莞市溪榜电子有限公司

DONG GUAN XI BANG ELECTRONICS CO., LTD.

单位	mm	投影		品名	Ac Inlet C14型	比例	Free
绘图	金泽杰	核对	张金龙	型号			
日期	2022/4/6	核准	周培培	料号	XB-0070ST-A01-003J1-DV1		

REV.	DATE	REVISION DESCRIPTION	ISSUE