

RoHS Compliant

REV.	DESCRIPTION	REVISER	DATE
A/0	INITIAL RELEASE.	WXB	2019.04.16

NOTES:

1.MATERIAH SEE THE TABLE.

2.MECHANICAL CHARAL
INSERTION FORCE: 44.1N MAX
EXTROCTION FORCE: 9.8N MIN, 39.2N MAX
DURABILITY: 10000 CYCLES AT
100±50 CYCLES PER HOUR

3.ELECTICAL CHARACTERISTICS
RATING CURRENT: 0.5A
RATING VOLTAGE: 40V
DIELECTRIC STRENGTH:300V AC/1 MINUTE
INSULATION RESISTANCE:500V DC 100MΩ MIN
CONTACT RESISTANCE:30 mΩ MAX.

4.AMBIENT TEMPERATURE: -45°C TO +105°C

5." * " FOR MAJOR DIM

6.PART NO.:

YUHONG
COMPANY

HDMI SERIES

AM: _____
A TYPE MALE

PIN NUMBER _____
19: 19PIN

HOUSNIG COLORE _____
B:BLACK L:BLUE

PACKING MODE
B:PE BAG T:TRAY

SERIAL NO _____

WELDING TYPE
1:SOLDER 2:STRADDLE

CONTACT PLATED
1: 1U" 5: 5U" F: 15U"

SHELL PLATED
A: AU N: NI

焊盘加锡厚度: 0.15±0.08

5	PCB	1	Fr4	T=1.6mm;green
4	SHELL	1	SPCC	T=0.4mm
3	CONTACT	19	COPPER ALLOY C5191	T=0.20mm
2	HOUSING	1	LCP BLACK	UL 94V-0
1	MOLDING	1	LCP BLACK	UL 94V-0
No.	PART NAME	QTY	MATERIAL	REMARK

XB 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.		品名 (ITEM NO)	HDMI A公 有筋 带板 19PIN 铁壳镀镍	
		料号 (PART NO)	XB-HDMI -08B	
单位(UNIT): MM	未注公差 TOLERANCE UNSPECIFIED	版次(REV): A/0	页次 (PAGE): 1/1	设计 (DESIGN) LIUMINGQIANG
比例(SCALE) 1:1	X.X ± 0.30 X.XX ± 0.20 X.XXX ± 0.10 X' ± 5' X.X' ± 2'	模号(MODEL NO)	XB-HDMI -08B	审核(CHECKED) CHUANDONG
图号(DWG NO)				核准(APPROVED) WUXIAOBIN