




SCHEMATIC (NON-SHORTING)



SPECIFICATIONS

Rating	3A 250V AC;6A 125 AC
FUNCTION	1P-4T
Contact Resistance	50MΩ Max
Insulation Resistance	100MΩ Min
Operating Force	400gf±100gf
Operating Life	10,000cycle

Model No	X (mm)
XB-T26-K2411-5P-G2	2mm
XB-T26-K2411-5P-G3	3mm
XB-T26-K2411-5P-G4	4mm
XB-T26-K2411-5P-G5	5mm
XB-T26-K2411-5P-G6	6mm
XB-T26-K2411-5P-G7	7mm
XB-T26-K2411-5P-G8	8mm
XB-T26-K2411-5P-G9	9mm
XB-T26-K2411-5P-G10	10mm

7	STEEL BALL	STEEL	1	NATURAL
6	SPRING	STEEL WIRE	1	NATURAL
5	CONTACT	BRASS	1	Ag PLATED
4	TERMINAL	BRASS	5	Ag PLATED
3	CASE	PA66	1	BLACK
2	COVER	PA66	1	BALCK
1	KNOB	PA66	1	BALCK
NO	PARTS	MATERIALS	Q' TY	FINISH

6	新增Rating选项		
5	更新样式		
4	更新Rating		
3	更新Rating		
2	新增SPEC		
1	更新封面		
ITEM NO.	DESCRIPTION	DRAWN	DATE

XB 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.3
Above 5 - 15 ±0.4
Above 15 - 30 ±0.5
Above 30 - 50 ±0.6
Angle ±0.5

3RD. ANGEL'S



UNITS

MM

DRAWN BY: PENG GAO
CHECKED BY: ZENG CHEN
APPROVED BY: ZENG CHEN
DATE: 01/29/24

MAT'L
FINISH
SCALE
SHEET NO.

TI' TLE
MODLE
DWG NO.
PART NO.

1:1
XB-T26-K2411-5P
1 of 1

SIZE
A4
VER