







ROHS



Switch Specifications
 Rating: 5A 250VAC ;
 2A 36VDC ;
 Degree of protection: IP67;
 Contact Resistance: 50mΩ Max. ;
 Dielectric Strength: 1000VAC For 1 minute ;
 Total Travel: 2.8±0.5mm ;
 Operating Force: 600±200gf ;
 Mechanical Life: 200,000 cycles ;
 Load Life: 50,000 cycles ;
 Operating Temperature: -20° C~85° C ;
 Function: OFF-(ON)



Panel Thickness: 10mm MAX.

MATERIAL:
 Actuator: SUS ;
 Top Base: SUS;
 Bottom Base: PA66+GF ;
 Terminal: Brass, Silver plated ;
 Nut: Brass, Ni plated .

The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing is subjected to change for improvement without prior notice.

LED Specifications

LED 类型	双向LED灯珠（交直流通用）			灯发光颜色 X Emitted color X		最小	一般	最大	额定 电流 (mA)
寿命	40000小时（参考值）			U3	蓝色	2.8	3.0	3.4	15
额定电压	AC/DC12V	AC/DC24V	AC/DC110V	G3	纯绿色	2.8	3.0	3.4	15
	AC/DC36V	AC/DC48V	AC/DC220V	Y2	黄色	1.8	2.0	2.4	15
额定电流	约15mA		约3mA	R2	红色	1.8	2.0	2.4	15
	采用3V灯，需内置电阻			顺向电压(V)					
降压方式									

W6	白色	5.0	6.0	9.0	15
U6	蓝色	5.0	6.0	9.0	15
G6	纯绿色	5.0	6.0	9.0	15
Y6	黄色	5.0	6.0	9.0	15
R6	红色	5.0	6.0	9.0	15
W3	白色	2.8	3.0	3.4	15

 Switch Connector		东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO.,LTD														
		TITLE : METAL PUHS BUTTON SWITCH						MODEL : XB-PBM22-12M-P-RR3-S0								
UNIT : MM		DWN.	ZENQ. CHEN	DATE		TOLERANCE <=1.5mm±0.1 > 1.5mm±0.2 >=10mm±0.3	ANGLE ±2°									
SCALE : 3 : 1		CHK'D	PENG. GAO	DATE												
VERSION	01	APPD.	FEI. LONG. HE	DATE												
								7	SPRING	STEEL WIRE	1	NATURE				
								6	STEEL BALL	STEEL	1	NATURE				
								5	BOARD	PHENOLIC RESIN	1	NATURE				
								4	CONTACT CLIP	PBS STRIP	2	Ag PLATED				
								3	FRAME	IRON STRIP	1	Ni PLATED				
								2	TERMINAL	BRASS STRIP	8	Ag PLATED				
								1	KNOB	POM	1	BLACK				
								NO.	PART NAME	MATERIAL	QTY.	FINISHING				