





# ROHS



SLIDE SWITCH 1P2T



## SPECIFICATION (INITIAL)

|                        |                                |
|------------------------|--------------------------------|
| RATING:                | DC 50V 0.5A                    |
| CONTACT RESISTANCE     | Not more than 30mΩ             |
| INSULATION RESISTANCE: | 500MΩ at 500V DC               |
| WITHSTAND VOLTAGE:     | AC 500V for 1 min              |
| OPERATION FORCE:       | 300±150g                       |
| SWITCHING LIFE:        | 10,000 Cycles(6-10c/m loading) |


The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.



东莞市溪榜电子有限公司  
DONG GUAN XI BANG ELECTRONICS CO., LTD

TITLE : XB SLIDE SWITCH

MODEL : XB-SS-12F12X



TOLERANCE  
≤1.5mm±0.1  
> 1.5mm±0.2  
>10mm±0.3

ANGLE  
±2°

|               |       |            |               |      |
|---------------|-------|------------|---------------|------|
| UNIT : MM     | DWN.  | ZENQ. CHEN | DATE          |      |
| SCALE : 3 : 1 | CHK'D | PENG. GAO  | DATE          |      |
| VBRSION       | 01    | APPD.      | FEI. LONG. HE | DATE |

|     |              |                |      |           |
|-----|--------------|----------------|------|-----------|
| 7   | SPRING       | STEEL WIRE     | 1    | NATURE    |
| 6   | STEEL BALL   | STEEL          | 1    | NATURE    |
| 5   | BOARD        | PHENOLIC RESIN | 1    | NATURE    |
| 4   | CONTACT CLIP | PBS STRIP      | 2    | Ag PLATED |
| 3   | FRAME        | IRON STRIP     | 1    | Ni PLATED |
| 2   | TERMINAL     | BRASS STRIP    | 8    | Ag PLATED |
| 1   | KNOB         | POM            | 1    | BLACK     |
| NO. | PART NAME    | MATERIAL       | QTY. | FINISHING |