

X=

3 TRAVEL

3.5

X

5.8

7.0

XB

TYP

1.0

3 3 3 3 3 3

4.2

9.8

THK
0.5

0.4^{NX}

5.3

X B

10.0

18.8

23.0

SLIDE SWITCH 2P6T

SPECIFICATION (INITIAL)	
RATING:	DC 50V 0.5A
CONTACT RESISTANCE:	Not more than 30mΩ
INSULATION RESISTANCE:	500MΩ at 500V DC
WITHSTAND VOLTAGE:	AC 500V for 1 min
OPERATION FORCE:	350±150g
SWITCHING LIFE:	10000cycles(6-10c/m loading)

SCHMATIC

The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.

 Switch Connector		东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO.,LTD									
		TITLE : XB SLIDE SWITCH									
		MODEL : XB-SS-26F01X									
UNIT : MM	DWN.	ZENQ. CHEN	DATE		TOLERANCE $\leq 1.5\text{mm} \pm 0.1$ $> 1.5\text{mm} \pm 0.2$ $> 10\text{mm} \pm 0.3$	ANGLE $\pm 2^\circ$	7	SPRING	STEEL WIRE	1	NATURE
SCALE : 3 : 1	CHK'D	PENG. GAO	DATE				6	STEEL BALL	STEEL	1	NATURE
VERSION	01	APPD.	FEI. LONG. HE	DATE				5	BOARD	PHENOLIC RESIN	1
							4	CONTACT CLIP	PBS STRIP	2	Ag PLATED
							3	FRAME	IRON STRIP	1	Ni PLATED
							2	TERMINAL	BRASS STRIP	8	Ag PLATED
							1	KNOB	POM	1	BLACK
							NO.	PART NAME	MATERIAL	QTY.	FINISHING