




开孔尺寸

SPECIFICATION (INITIAL)					
RATING: 10A 12A 125V 250V AC					
CONTACT RESISTANCE: Not more than 30mΩ					
INSULATION RESISTANCE:500MΩ at1500V DC					
WITHSTAND VOLTAGE:AC 500V for 1 min					
OPERATION FORCE: 300±100g					
SWITCHING LIFE:10000 Cycles(6-10c/m loading)					

序号	名称	数量	材料	型号	阻燃
1	基座	1	PA66	EPR27L	V0级
2	推子	1	PA66	EPR27L	V0级
3	盖板	1	铁皮		
4	焊脚	3	黄铜电镀		
5	弹簧	2	碳素钢丝		

The material contained in this drawing is the property of XiBang. Any use other than that specfically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.

 Switch Connector	东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO.,LTD															
	TITLE : XB SLIDE SWITCH															
	MODEL : XB-CH-Z07															
UNIT : MM		DWN.	ZENQ. CHEN	DATE			TOLERANCE <=1.5mm±0.1 > 1.5mm±0.2 >=10mm±0.3	ANGLE ±2°								
SCALE : 3 : 1		CHK'D	PENG. GAO	DATE												
VERSION	01	APPD.	FEI. LONG. HE	DATE												
</																