


Recommended P.C.B Layout

Layout Tolerance=+/-0.05mm



REV.	DESCRIPTION	DRAW.	DATE.

No: of pins	Dimension				
	DIM.A	DIM.B	DIM.C	DIM.D	DIM.E
02	7.00	5.10	2.00	4.35	2.00
03	9.00	7.10	4.00	6.35	4.00
04	11.00	9.10	6.00	8.35	6.00
05	13.00	11.10	8.00	10.35	8.00
06	15.00	13.10	10.00	12.35	10.00
07	17.00	15.10	12.00	14.35	12.00
08	19.00	17.10	14.00	16.35	14.00
09	21.00	19.10	16.00	18.35	16.00
10	23.00	21.10	18.00	20.35	18.00
11	25.00	23.10	20.00	22.35	20.00
12	27.00	25.10	22.00	24.35	22.00

Material

Insulator:Nylon 9T(UL94V-0)

Contact:phosphor Bronze

Contact Plated:Gold over Nickel or Tin

Specification

Current rating:7A

instant CURRENT:10A

Contact Resistance:30mΩ

Insulation Resistance:100MΩ

Dielectric Voltage:500V

Operdting Temperature:-40°~105°

XB 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

UNLESS OTHERWISE
SPECIFIED,TOLERANCE:
X. ±0.20
X.x ±0.15
X.xx ±0.10
ANGULAR ±2°

DESIGN	Y.Q.H	DATE	2014.08.26	TITLE:	
APPROVED		DATE			
PART NO	XB-C-B01F-B-S2-1.6#		REV: 01	SCALE: 1:1	UNIT:mm
DRAWING NO			SIZE: A4	SHEET: 1/1	