







ROHS



PCB LAYOUT MOUNTING PATTERN



SCHEMATIC



SPECIFICATIONS

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.3 ± 0.1mm
Operating Force	75gf ± 5gf
Operating Life(cycles)	100,000

5	HS86. 0428. 035-5	按钮	1	PPA
4	HS86. 0428. 018-4	按垫	1	橡胶
3	HS86. 0428. 030-3	盖板	1	PPA(黑)
2	HS86. 0428. 005-2	簧片	1	不锈钢复银
1	HS86. 0428. 025-1	底座组	1	PPA(黑)黄铜带H65Y0.3mm
序号	编号	材料	数量	材料

The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing is subjected to change for improvement without prior notice.

XB Switch Connector 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO.,LTD																
TITLE : XB TACT SWITCH																
MODEL : XB-TS-4DV045 贴片轻触开关 贴片按键开关6.2x6.2x4.5																
UNIT : MM		DWN.		DATE		TOLERANCE		ANGLE TOL								
SCALE : 5 : 1		CHK'D		DATE		<=1.5mm ± 0.1										
						> 1.5mm ± 0.2										
VERSION		01	APPD.		DATE		>=10.0mm ± 0.3		± 2°							