





123456789



Specifications
Current Rating:3.0Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:600VAC
Contact Resistance:20mΩMax.
Operating Temperature:-40°C to +105°C
Materials
Contact Material:
Brass(Pin length less than 25mm)
Phosphor Bronze(The total length of pin is more than 25mm)
Insulator Material:
PBT(Not resistant to high temperature), Nylon(High temperature resistance), LCP(High temperature resistance),
UL 94V-0

Recommended P.C.Board
Layout
(Tolerance:±0.05)



No. of PIN/ROW	Dimension Information	
	M	L
02	2.54	4.96
03	5.08	7.50
04	7.62	10.04
05	10.16	12.58
06	12.70	15.12
07	15.24	17.66
08	17.78	20.20
09	20.32	22.74
10	22.86	25.28
11	25.40	27.82
12	27.94	30.36
13	30.48	32.90
14	33.02	35.44
15	35.56	37.98
16	38.10	40.52
17	40.64	43.06
18	43.18	45.60
19	45.72	48.14
20	48.26	50.68
21	50.80	53.22
22	53.34	55.76
23	55.88	58.30
24	58.42	60.84
25	60.96	63.38
26	63.50	65.92
27	66.04	68.46
28	68.58	71.00
29	71.12	73.54
30	73.66	76.08

Ordering Information

XB-PZ-A-254-304

Plastic specifications
1=Single row
2=Dual row
3=Tripe row
4=Quadruple

Water code

No. of Pins per Row
02~30

Positioning column information
A=No locating post
B=Round post
C=Square post
Plating code
01=Tin
02=Gold Flash
05=Gold Flash/Tin
22=Matte Tin

Pin length
See the drawing

Insulator Material
A=PBT
R=Nylon(Halogen Free)
C=LCP

Color
1=Black
2=White
3=Yellow
E=Beige

Contact Material
A/S/K/T=Phosphor Bronze
B/Z/H/W=Brass

Packing code
A=Box
B=Tray
C=Tube
D=Tape&Reel
E=Cap+Tube
F=Cap+Tape&Reel
G=Acetate Tape+Tube
H=Acetate Tape+Tape&Reel

Dim.D	NOTE
5.00	02Pins
6.50	03~30Pins

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV. 01 UNIT. mm SCALE. 3:1 PAGE. 1/1

GENERAL TOLERANCE

X.°±5.0°	X.±0.30
.X°±3.0°	.X±0.25
.XX°±2.0°	.XX±0.15
.XXX°±1.0°	.XXX±0.10

DWG. NO. XB-PZ-A-254-304
PART NO. XB-PZ-A-254-304

TITLE. 2.54 PIN HEADER
THREE ROWS DIP TYPE
CONNECTOR

123456789