

Notes:

Insulator: Glass filled Polyester UL 94V-0

① Shell: Steel, Nickel plated as standard

Coaxial terminal

Insulator:Teflon UL 94V-0 Color white

Contact:Brass with Gold plated

* For Lead Free Wave Flow Process

Ordering Code

3W3C	S	C	V	3	0	1	75	D00
①	②	③	④	⑤	⑥	⑦	⑧	⑨

① Series No.

② Connector Type:
S= Receptacle (2 Female + 1 Male Contacts)

③ Contact type: C= Coaxial Contact

④ Contact tail style: V= Straight Dip type

⑤ Coaxial contact plating:
2= Gold flash plated over Nickel
3= 15μ" Gold plated over Nickel
4= 30μ" Gold plated over Nickel
5= 50μ" Gold plated over Nickel

⑥ Signal contact plating:
0= Without signal contact

⑦ Insulator color: 1= Black, 6= Green

⑧ Performance: 50= 50Ω, 75= 75Ω

⑨ Mounting Style:
000= With Ø3.05mm holes on shell
B00= Riveted #4-40 UNC open nuts on front shell
C00= Riveted #4-40 UNC open nuts on rear shell
D00= Riveted #4-40 UNC ground stand-off on rear shell (standard)

Lead Free Process

RoHS Compliant

4					DATE	UNIT: mm / inch		TITLE: 3W3C MALE COAXIAL D-SUB CONNECTOR (TOP ENTRY BOARD MOUNT TYPE)	X3 Switch Connector 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD	
3				DRAWN BY:	Karen	1/17-18'	TOLERANCE UNLESS OTHERWISE SPECIFIED			
2				ENGINEER:	Sun	1/23-18'				
1	Karen	1/17-18'	ECNT117262/ECRT117074	CHECKED BY:	Eisley	1/25-18'				
SYM	NAME	DATE	REVISIONS	APPROVED BY:	Eisley	1/25-18'	.X ± 0.30/.012 .XX ± 0.20/.008 .XXX ± 0.10/.004	X: ± .1 .X ± .XX ±	MATERIAL:	
								FINISH:	DRAWING NO. 3W3C13SB	PART NO. 3W3CSCV*0****00
								SCALE 2 / 1	SHEET 1 OF 1	