




Material:

Insulator: Glass filled Polyester UL 94V-0

Shell: Steel, Tin plated as standard

Coaxial terminal

Insulator: Teflon UL 94V-0



Color white

Contact: Brass with Gold plated

Ordering Code

C5W5 P C H 3 0 1 75 I10
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type: P= Plug
- ③ Contact type: C= Coaxial Contact
- ④ Contact tail style: H= Right Angle Dip type
- ⑤ Coaxial contact plating:
2= Gold flash plated over Nickel
3= 15μ" Gold plated over Nickel
4= 30μ" Gold plated over Nickel
5= 50μ" Gold plated over Nickel
- ⑥ Singal contact plating:
0= Without singal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 50= 50Ω, 75= 75Ω
- ⑨ Mounting Style:
000= With ø3.05mm holes on shell
B00= Riveted #4-40 UNC open nuts on front shell
C00= Riveted #4-40 UNC open nuts on rear shell
I00= Riveted #4-40 UNC ground tabs with ø3.2mm holes
I10= Riveted #4-40 UNC ground tabs with board locks(standard)



Mounting Style

Code	000	Code	B00	Code	C00	Code	I00	Code	I10
	DIM. L= 4.0mm		DIM. L= 4.0mm		DIM. L= 4.0mm		øA=3.2mm		

Recommended P.C Board Layout

4					DATE	UNIT: mm / inch		TITLE: C5W5 COAXIAL MALE D-SUB CONNECTOR (RIGHT ANGLE BOARD MOUNT TYPE)	X3 Switch Connector 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.						
3				DRAWN BY:	Karen	3/20-17'	TOLERANCE UNLESS OTHERWISE SPECIFIED			MATERIAL:	DRAWING NO.	C5W505SC	PART NO.	C5W5PCH*0*****	
2				ENGINEER:	Sun	3/20-17'	.X ± 0.30/.012								X' ± 1'
1	Karen	3/20-17'	ECNT117049/ECRT117003	CHECKED BY:	Eisley	3/22-17'	.XX ± 0.20/.008								X' ±
SYM	NAME	DATE	REVISIONS	APPROVED BY:	Eisley	3/22-17'	.XXX ± 0.10/.004	.XX ±	FINISH:	SCALE	2 / 1	SHEET	1	OF	1