



RECOMMENDED PCB LAYOUT
TOP VIEW (. XX ± 0.05)

性能:

- 额定电流: 2.0A
- 额定电压: 12V
- 耐电压: 500V
- 接触电阻: 30m Ω
- 绝缘电阻: 500M Ω
- 工作温度: -40 $^{\circ}$ C ~ +85 $^{\circ}$ C
- 塑件 (材质): LCP
- 接触点 (材质): 磷铜, 镀金3u

版本REV.	更新标记REVISION	NOTE	日期DATE	未注公差 TOLERANCE	东莞市溪榜电子有限公司 Switch Connector DONG GUAN XI BANG ELECTRONICS CO., LTD	
				X. XX ± 0.35	X. * $\pm 1^{\circ}$	品名ARTICLE: 弹片电池座连接器 Bullet Batteryholderconnector
				X. X ± 0.25	X. X' $\pm 0.5^{\circ}$	
				X. XX ± 0.15	X. XX ± 0.05	
绘制DRAWN	高鹏			X. XXX ± 0.05	X. XXX $\pm 0.005^{\circ}$	图号MODEL: XB-BC-80-4PD300-2P A4
设计DES' D	庞东			视图方法 PROJECTION		
审核CHK' D	贺龙飞			比例SCALE:		单位UNIT: mm 页码SHEET: 共1页 第1页
批准APPV' D	杨军					